

FIG.2




FIG.3




FIG.4




FIG. 5




FIG.7




FIG.8





FIG.9



2025 RELEASE UNDER E.O. 14176

FIG.10




FIG.11




FIG.12




FIG.13




FIG. 14




[illegible]

FIG.15




2025 RELEASE UNDER E.O. 14176

FIG.16



Patent Application No. 2001-000000

FIG. 17






FIG.19




FIG.20

Pw (mW)	beta (%)	B
10	-20	1000
11	-14	800
12	-12	700
13	-8	500
14	-3	450
15	1	400
16	5	380
17	7	340
18	10	310
19	13	280

FIG.21




FIG.22

TYPE	VELOCITY (x)	F1	F2	theta (T)
1	12	1.00	1.00	0.00
1	16	1.10	1.00	0.10
1	20	1.15	1.00	0.20
1	24	1.20	1.00	0.30
2	12	1.00	1.00	0.10
2	16	1.20	1.10	0.10
2	20	1.40	1.20	0.10
2	24	1.60	1.30	0.20
...




FIG.23

FIG.24

MANUFACTURER ID CODE	TYPE CODE	RECORDING PARAMETER NUMBER
A	0	1
A	1	1
A	2	2
A
B	0	3
B	1	4
B	2	4
B
...

1.0250250 077322000